

"APPENDIX A – AMENDED March 22, 2007

"PROPOSED RULE CHANGES

"Part 97 of Chapter I of Title 47 of the Code of Federal Regulation is proposed to be amended as follows:

"Section 97.3(a)(8) is amended to read as follows:

"(8) Bandwidth. For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions (See the definition of Necessary Bandwidth in Section 2.1 of this Chapter and Section 97.101(a) of this Part).

"Section 97.3(a)(42) is amended to read as follows:

"(42) Spurious Emission. For the purposes of this Part, emission on a frequency or frequencies which are outside the allocated frequency band and which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products.

"Section 97.119 is amended to read as follows:

"§ 97.119 Station identification.

\*\*\*\*\*

"(b)...

(1) By a CW or MCW emission. When keyed by an automatic device used only for identification, the speed must not exceed 20 words per minute;

(2) Where phone emissions are permitted, by a phone emission in the English language. Use of a standard phonetic alphabet as an aid for correct station identification is encouraged;

(3) By the same emission as used for the communication.

(4) (Deleted)

"Section 97.305 is amended to read as follows:

"§ 97.305 Authorized emission types.

\*\*\*\*\*

"(b) A station may transmit a test emission on any frequency authorized to the control operator for brief periods for experimental purposes. Test transmissions are authorized in the segments 51-54 MHz, 144.1-148.0 MHz and on all bands above 222 MHz.

"(c) Pulse emissions are permitted on all bands authorized to the control operator above 902 MHz except in the 23 cm and 3 cm bands.

"(d) SS emissions are permitted on all bands authorized to the control operator above 222 MHz.

"(e) A station may transmit the following emission types on the frequencies indicated, as authorized to the control operator, subject to the standards specified in § 97.307(f) of this part; except that on frequencies below 28.0 MHz, a Station having a control operator holding a Novice Class or Technician Class operator license may only transmit a CW emission using the international Morse code.

"Wavelength band Frequencies Emission Types Authorized Standards, see §97.307(f), paragraph:

MF:

160 m Entire band RTTY, data (3)

-do- -do- Phone, image (1), (2)

"HF:

80 m Entire band RTTY, data (3)

75 m Entire band Phone, image (1), (2)

40 m 7.000-7.125 MHz RTTY, data (3)

40 m 7.075-7.100 MHz Phone, image (1), (2), (4)

40 m 7.125-7.300 MHz Phone, image (1), (2)

30 m Entire band RTTY, data (3)

20 m 14.00-14.15 MHz RTTY, data (3)

-do- 14.15-14.35 MHz Phone, image (1), (2)

17 m 18.068-18.110 MHz RTTY, data (3)

-do- 18.110-18.168 MHz Phone, image (1), (2)

15 m 21.0-21.2 MHz RTTY, data (3)

-do- 21.20-21.45 MHz Phone, image (1), (2)

12 m 24.89-24.93 MHz RTTY, data (3)

-do- 24.93-24.99 MHz Phone, image (1), (2)

"(f) Except as otherwise provided in this Section, a station may transmit any emission on any frequency authorized to the control operator subject to the following bandwidth limitations:

Wavelength

band Frequencies authorized Maximum bandwidth Standards

See §97.307(f) paragraph:

10 m 28.00-28.05 MHz 200 Hz

-do- 28.05-28.120 MHz 500 Hz

-do- 28.120-29.0 MHz 3 kHz (5)

-do- 29.0-29.7 MHz 16 kHz

6 m 50.0-50.1 MHz 200 Hz

-do- 50.1-50.3 MHz 3 kHz

-do- 50.3-54 MHz 100 kHz

2 m 144.0-144.1 MHz 200 Hz

-do- 144.1-144.3 MHz 3 kHz

-do- 144.3-148.0 MHz 100 kHz

1.25 m 219-220 MHz 100 kHz

-do- 222-225 MHz - (6)

70 cm Entire band - (6)

33 cm Entire band - (6)

23 cm Entire band - (6)  
13 cm Entire band - (6)  
9 cm Entire band - (6)  
5 cm Entire band - (6)  
3 cm Entire band - (6)  
1.2 cm Entire band - (6)  
6 mm Entire band - (6)  
4 mm Entire band - (6)  
2.5 mm Entire band - (6)  
1 mm Entire band - (6)  
- Above 275 GHz -

"Section 97.307(f) is amended to read as follows:

"§ 97.307 Emission standards.

\*\*\*\*\*

"(f) The following standards and limitations apply to transmissions on the frequencies specified in § 97.305(e) and (f) of this Part.

- (1) No angle-modulated emission may have a modulation index greater than 1 at the highest modulation frequency.
- (2) No non-phone emission shall exceed the bandwidth of a communications quality phone emission of the same modulation type. The total bandwidth of an independent sideband emission (having B as the first symbol), or a multiplexed image and phone emission, shall not exceed that of a communications quality A3E emission.
- (3) The bandwidth of a RTTY or data emission must not exceed 3 kHz.
- (4) Phone and image emissions may be transmitted only by stations located in ITU Regions 1 and 3, and by stations located within ITU Region 2 that are west of 130° West longitude or south of 20° North latitude.
- (5) The 3 kHz maximum bandwidth does not apply to double-sideband amplitude-modulated phone A3E emissions.
- (6) No specific bandwidth limitations apply except that the entire emission must be within the allocated band to meet the requirements of §97.307(d).

"Section 97.309 is amended to read as follows:

"§ 97.309 RTTY and data emission codes.

"(a) Where authorized by §97.305(e) and (f), an amateur station may transmit a RTTY or data emission using published digital codes for the purpose of facilitating communications.

"(b) When deemed necessary by the FCC's Enforcement Bureau to assure compliance with the FCC Rules, a station must:

- (1) Restrict transmissions of any digital code to the extent instructed; and
- (2) Maintain a record, convertible to the original information, of all digital communications transmitted."